



JJV10D820K	JJV10D820KJ	50	65	16.8	17.0	2500	1250	3500	2500	0.4	82(74-90)	135	1200
JJV10D101K	JJV10D101KJ	60	85	18.2	18.5	2500	1250	3500	2500	0.4	100(90-110)	165	1000
JJV10D121K	JJV10D121KJ	75	100	21.0	21.5	2500	1250	3500	2500	0.4	120(108-132)	200	830
JJV10D151K	JJV10D151KJ	95	125	15.2	26.0	2500	1250	3500	2500	0.4	150(135-165)	250	670
JJV10D181K	JJV10D181KJ	115	150	30.8	38.0	2500	1250	3500	2500	0.4	180(162-198)	300	560
JJV10D201K	JJV10D201KJ	130	170	42.0	42.5	2500	1250	3500	2500	0.4	200(185-225)	330	500
JJV10D221K	JJV10D221KJ	140	180	46.2	46.5	2500	1250	3500	2500	0.4	220(198-242)	360	450
JJV10D241K	JJV10D241KJ	150	200	50.4	51.0	2500	1250	3500	2500	0.4	240(216-264)	395	420
JJV10D271K	JJV10D271KJ	175	225	57.4	58.0	2500	1250	3500	2500	0.4	270(243-297)	455	370
JJV10D301K	JJV10D301KJ	190	250	63.0	63.5	2500	1250	3500	2500	0.4	300(270-330)	505	330
JJV10D331K	JJV10D331KJ	210	275	68.6	69.0	2500	1250	3500	2500	0.4	330(297-363)	550	300
JJV10D361K	JJV10D361KJ	230	300	74.2	75.0	2500	1250	3500	2500	0.4	360(324-396)	595	280
JJV10D391K	JJV10D391KJ	250	320	81.2	82.0	2500	1250	3500	2500	0.4	390(351-429)	650	260
JJV10D431K	JJV10D431KJ	275	350	88.2	89.0	2500	1250	3500	2500	0.4	430(387-473)	710	230
JJV10D471K	JJV10D471KJ	300	385	96	100	2500	1250	3500	2500	0.4	470(423-517)	775	210
JJV10D511K	JJV10D511KJ	320	415	98	102	2500	1250	3500	2500	0.4	510(459-561)	845	200
JJV10D561K	JJV10D561KJ	350	460	100	104	2500	1250	3500	2500	0.4	560(504-616)	920	180
JJV10D621K	JJV10D621KJ	385	505	102	106	2500	1250	3500	2500	0.4	620(558-682)	1025	160
JJV10D681K	JJV10D681KJ	420	560	104	108	2500	1250	3500	2500	0.4	680(612-748)	1120	150
JJV10D751K	JJV10D751KJ	460	615	110	118	2500	1250	3500	2500	0.4	750(675-825)	1240	140
JJV10D781K	JJV10D781KJ	485	640	118	120	2500	1250	3500	2500	0.4	780(702-858)	1290	130
JJV10D821K	JJV10D821KJ	510	670	122	125	2500	1250	3500	2500	0.4	820(738-902)	1355	120
JJV10D911K	JJV10D911KJ	550	745	128	134	2500	1250	3500	2500	0.4	910(819-1001)	1500	110
JJV10D102K	JJV10D102KJ	625	825	131	140	2500	1250	3500	2500	0.4	1000(900-1100)	1650	100
JJV10D112K	JJV10D112KJ	680	895	133	155	2500	1250	3500	2500	0.4	1100(990-1210)	1815	90



RELIABILITY TESTS Environmental ratings

Dry Heat Loading	The specimen shall be applied continuously the maximum allowable voltage at the specified conditions for specified period and then stored at room temperature and normal humidity over 2 hours. Thereafter the change of V_B and mechanical damage shall be examined. Ambient temp.: 125 ± 2 ; Period: 1000 ± 24 hours.	$V_B/V_B\% \pm 10\%$
High Temperature Storage	In a drying oven without load. Ambient temp.: 125 ± 2 ; period: 1000 ± 24 hours	$V_B/V_B\% \pm 5\%$
Damp Heat Loading	The specimen shall be applied continuously the maximum allowable voltage at the specified conditions for specified period and then stored at room temperature and normal humidity over 2 hours. Thereafter, the change of V_B and mechanical damage shall be examined.	



DIMENSIONAL DRAWINGS

Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
D						0.571
L				0.591		
d	0.75		0.85	0.030		0.033
F	6.7		8.3			
H			16.0			

JJV10D102K

T



JJV10D

180L to 781K

500ar

-- 9 ' ð W R





JJV10D471K-10D112K (N/J series)

JieJie products are not designed for, and shall not be used for, any purpose (including, without limitation, automotive, military, aerospace, medical, life-saving, life-sustaining or nuclear facility applications, devices intended for surgical implant into the body, or any other application in which the failure or lack of desired operation of the product may result in personal injury, death, or property damage) other than those expressly set forth in applicable JieJie product documentation. Warranties granted by JieJie shall be deemed void for products used for any purpose not expressly set forth in applicable JieJie documentation. JieJie shall not be liable for any claims or damages arising out of products used in applications not expressly intended by JieJie as set forth in applicable JieJie documentation. The sale and use of JieJie products is subject to JieJie terms and conditions of sale, unless otherwise agreed by JieJie.

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu