



JX080A 8A SSCR

Rev A.1.1

DESCRIPTION:

1. 8A SSCR  
 2. V<sub>RRM</sub> 800V  
 3. I<sub>TRM</sub> 8A  
 4. I<sub>TC</sub> 20A  
 5. T<sub>95</sub> 175°C  
 6. V<sub>CE</sub> 800V  
 7. I<sub>CE</sub> 8A  
 8. I<sub>TC</sub> 20A  
 9. T<sub>95</sub> 175°C  
 10. V<sub>CE</sub> 800V  
 11. I<sub>CE</sub> 8A  
 12. I<sub>TC</sub> 20A  
 13. T<sub>95</sub> 175°C

MAIN FEATURES

I <sub>TRM</sub>	8	A
V <sub>RRM</sub> / V <sub>CE</sub>	800	V
I <sub>TC</sub>	20	A

ABSOLUTE MAXIMUM RATINGS

P <sub>tot</sub>	S <sub>tot</sub>	V <sub>CE</sub>	U <sub>h</sub>
1.5W	T <sub>95</sub>	-0.6	

**JX080A**

**Jè J**



**JX080A**



**ORDERING INFORMATION**

Ord	V <sub>g</sub> V <sub>DRM</sub> /V <sub>RRM</sub> (V)	IGT \$	P <sub>g</sub>	Be <sub>g</sub> (P)	D <sub>g</sub> th
JX080A	800	"200	TO-220A(I <sub>p</sub> )	50	T <sub>h</sub>

**DRH**

D	R	G
M 8 , 02 3	A 1.0	#
0 ., 02	A 1.1	Rè



