



T0610H-6C 6A TRIAC

Rev.A.1.1

## DESCRIPTION:

The T0610H-6C triac is suitable for general purpose AC switching. It can be used as an ON/OFF function in applications such as heating regulation, induction motor starting circuits, for phase control operation in light dimmers, motor speed controllers. Compared to traditional triacs, T0610H-6C provides a very high switching capability up to junction temperatures of 150°C. It can be driven directly through the MCU I/O port. From T2 terminals to external heatsink. Package TO-220C is RoHS compliant.

## MAIN FEATURES

## ABSOLUTE MAXIMUM RATINGS


Parameter	Symbol	Value	Unit
Storage junction temperature range	$T_{stg}$	-40-150	
Operating			

Peak gate power	P <sub>GM</sub>	10	W
Peak pulse voltage (T <sub>j</sub> =25 ; non-repetitive,off-state;FIG.7)			

**ELECTRICAL CHARACTERISTICS** (unless otherwise specified)

Symbol	Test Condition	Quadrant	Value	Unit
I <sub>ES</sub>	V <sub>GS</sub> =12V R=33Ω	MAX.	10	mA

ORDERING INFORMATION



MARKING




FIG.1: Maximum power dissipation versus RMS on-state current




FIG.2: RMS on-state current versus case temperature






## ORDERING INFORMATION

Order code	Voltage $V_{DRM}/V_{RRM}$ (V)	IGT(mA)	Package	Base qty. (pcs)	Delivery mode
------------	----------------------------------	---------	---------	--------------------	------------------

PACKAGE MECHANICAL DATA C2C3



0 .