



JST06A-800CW 6A TRIAC

Rev.A.1.1

DESCRIPTION:

1. 800V
 2. 6A
 3. 800V
 4. 6A
 5. 800V
 6. 6A
 7. 800V
 8. 6A
 9. 800V
 10. 6A
 11. 800V
 12. 6A
 13. 800V
 14. 6A
 15. 800V
 16. 6A
 17. 800V
 18. 6A
 19. 800V
 20. 6A
 21. 800V
 22. 6A
 23. 800V
 24. 6A
 25. 800V
 26. 6A
 27. 800V
 28. 6A
 29. 800V
 30. 6A
 31. 800V
 32. 6A
 33. 800V
 34. 6A
 35. 800V
 36. 6A
 37. 800V
 38. 6A
 39. 800V
 40. 6A
 41. 800V
 42. 6A
 43. 800V
 44. 6A
 45. 800V
 46. 6A
 47. 800V
 48. 6A
 49. 800V
 50. 6A
 51. 800V
 52. 6A
 53. 800V
 54. 6A
 55. 800V
 56. 6A
 57. 800V
 58. 6A
 59. 800V
 60. 6A
 61. 800V
 62. 6A
 63. 800V
 64. 6A
 65. 800V
 66. 6A
 67. 800V
 68. 6A
 69. 800V
 70. 6A
 71. 800V
 72. 6A
 73. 800V
 74. 6A
 75. 800V
 76. 6A
 77. 800V
 78. 6A
 79. 800V
 80. 6A
 81. 800V
 82. 6A
 83. 800V
 84. 6A
 85. 800V
 86. 6A
 87. 800V
 88. 6A
 89. 800V
 90. 6A
 91. 800V
 92. 6A
 93. 800V
 94. 6A
 95. 800V
 96. 6A
 97. 800V
 98. 6A
 99. 800V
 100. 6A

MAIN FEATURES

ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Value	Unit
Storage Temperature	T_s	-40 to 100	°C
Junction Temperature	T_j	-40 to 125	°C
Peak Repetitive Forward Voltage (T _c = 25°C)	V_{FM}		
Peak Forward Voltage (T _c = 25°C)	V_{FM}		
Peak Reverse Voltage (T _c = 25°C)	V_{RM}		
Peak Forward Current (T _c = 25°C)	I_{FM}	6	
Peak Reverse Current (T _c = 25°C)		2	
Peak Forward Surge Current (T _c = 25°C)	I_{FSM}	2	2s
Peak Reverse Surge Current (T _c = 25°C)			

JST06A-800CW



ORDERING INFORMATION

Order code	Voltage V _{DRM} /V _{RRM} (V)	IGT(mA)	Package	Base qty. (pcs)	Delivery mode
		- -			
JST06A-800CW	800	35	TO-220A(Ins)	50	Tube

Document Revision History

Rev	Description	Author
A 03	A 10	##
A 11	Re	##

