


ELECTRICAL CHARACTERISTICS (unless otherwise specified)

Symbol Test Condition

ORDERING INFORMATION



MARKING




FIG.1: Maximum power dissipation versus RMS on-state current





FIG.2: RMS on-state current versus case temperature




JST134W-600T

ORDERING INFORMATION

| Order code | Voltage V_{DRM}/V_{RRM} (V) | IGT(mA) - I | Package | Base qty. (pcs) | Delivery mode |
|------------|----------------------------------|----------------|---------|--------------------|------------------|
|------------|----------------------------------|----------------|---------|--------------------|------------------|

JST134W-600T

DELIVERY MODE



| Ref. | Dimensions | | | | | |
|------|-------------|-------|-------|--------|-------|-------|
| | Millimeters | | | Inches | | |
| | Min. | Typ. | Max. | Min. | Typ. | Max. |
| W | - | - | 12.30 | - | - | 0.482 |
| E | 1.65 | 1.75 | 1.85 | 0.065 | 0.069 | 0.073 |
| F | 5.45 | 5.50 | 5.55 | 0.215 | 0.217 | 0.219 |
| D0 | 1.50 | 1.55 | 1.60 | 0.059 | 0.061 | 0.063 |
| D1 | 1.50 | - | - | 0.059 | - | - |
| P0 | 3.90 | 4.00 | 4.10 | 0.154 | 0.157 | 0.161 |
| P1 | 7.90 | 8.00 | 8.10 | 0.311 | 0.315 | 0.319 |
| P2 | 1.95 | 2.00 | 2.05 | 0.077 | 0.079 | 0.081 |
| 10P0 | 39.80 | 40.00 | 40.20 | 1.567 | 1.575 | 1.583 |
| A0 | 6.85 | 6.95 | 7.05 | 0.269 | 0.273 | 0.276 |
| B0 | 7.15 | 7.25 | 7.35 | 0.280 | 0.284 | 0.288 |
| K0 | 1.95 | 2.05 | 2.15 | 0.076 | 0.080 | 0.084 |
| T | 0.20 | 0.25 | 0.30 | 0.008 | 0.010 | 0.012 |

