




ORDERING INFORMATION

J	ST	24	E	-1200	BW	-/
JieJie Microelectronics Co., Ltd.	Triacs	$I_{T(RMS)}: 25A$	$E: TO-263$	$1200: V_{DRM} / V_{RRM} \geq 1200V$	$BW: I_{GT1-3} \leq 50mA$	Blank: Tube -TR: Tape & Reel

MARKING




FIG.7: Relative variations of gate trigger current, holding current and latching current versus junction temperature




FIG.8: Test circuit for inductive and resistive loads to IEC-61000-4-5 standards




JST24E-1200BW

PACKAGE MECHANICAL DATA

Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	9.90		10.20	0.390		0.402
B	14.70		15.80	0.579		0.622
C	9.40		9.60	0.370		0.378
D	2.40			0.094		
E	1.20		1.50	0.047		0.059
F	0.75		0.85	0.029		0.033

DELIVERY MODE



Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.

is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.

Copyright © 2025